Material Safety Data Sheet

1. CHEMICAL PRODUCTION IDENTIFICATION AND MANUFACTURER OR SUPPLIER DETAILS

Material Name : Shell Corena S3 R 46

Uses : Compressor oil. Product Code : 001D7782

Manufacturer/Supplier : Shell Oil Products Ukraine LLC

"Horizon Park" Business Center

4-B, N.Grinchenko str.

03038 Kiev Ukraine

Telephone : +38 044 459 03 77 **Fax** : +38 044 459 03 78

Emergency Telephone

Number

: +38 044 459 03 77

2. HAZARD IDENTIFICATION

EC Classification : Not classified as dangerous under EC criteria.

Health Hazards : Not expected to be a health hazard when used under normal

conditions. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful

impurities.

Signs and Symptoms : Oil acne/folliculitis signs and symptoms may include formation

of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

Safety Hazards : Not classified as flammable but will burn.

Environmental Hazards : Not classified as dangerous for the environment.

3. COMPOSITION (INFORMATION ABOUT THE COMPONENTS)

Mixture Description : Highly refined mineral oils and additives.

Hazardous Components

Chemical Identity	CAS	EINECS	Symbol(s)	R-phrase(s)	Conc.
Alkaryl amine	68411-46-1	270-128-1		R52/53	< 3,00 %

Additional Information : The highly refined mineral oil contains <3% (w/w) DMSO-

extract, according to IP346. Refer to chapter 16 for full text of

EC R-phrases.

according to EC directive 2001/58/EC

Material Safety Data Sheet

4. MEASURES OF FIRST AID

General Information Not expected to be a health hazard when used under normal

conditions.

Inhalation No treatment necessary under normal conditions of use. If

symptoms persist, obtain medical advice.

Skin Contact : Remove contaminated clothing. Flush exposed area with water

and follow by washing with soap if available. If persistent

irritation occurs, obtain medical attention.

Flush eye with copious quantities of water. If persistent **Eye Contact**

irritation occurs, obtain medical attention.

In general no treatment is necessary unless large quantities Ingestion

are swallowed, however, get medical advice.

Advice to Physician : Treat symptomatically.

5. MEASURES AND FACILITIES TO GUARANTEE FIRE AND EXPLOSION SAFETY

Clear fire area of all non-emergency personnel.

Typical 230 °C / 446 °F (COC) Flash point

Upper / lower Typical 1 - 10 %(V)(based on mineral oil)

Flammability or **Explosion limits**

Auto ignition temperature

: > 320 °C / 608 °F

Hazardous combustion products may include: A complex Specific Hazards

Do not use water in a jet.

mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic

compounds.

Suitable Extinguishing

Media

: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable Extinguishing

Media

Protective Equipment for

Firefighters

Print Date 17.11.2012

Additional Advice Fire resistant liquid.

Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

6. MEASURES ON PREVENTION AND LIQUIDATIONS OF EXTREME SITUATIONS AND ITS **OUTCOMES**

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations.

Protective measures : Avoid contact with skin and eyes. Use appropriate containment

> to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or

other appropriate barriers.

Clean Up Methods Slippery when spilt. Avoid accidents, clean up immediately.

Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an

000000019506

2/9

according to EC directive 2001/58/EC

Material Safety Data Sheet

absorbent. Soak up residue with an absorbent such as clay,

sand or other suitable material and dispose of properly.

Additional Advice : Local authorities should be advised if significant spillages

cannot be contained.

7. RULES OF CHEMICAL PRODUCTION STORAGE AND HANDLING OPERATIONS

General Precautions : Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage

and disposal of this material.

Handling : Avoid prolonged or repeated contact with skin. Avoid inhaling

vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or

cleaning materials in order to prevent fires.

Storage : Keep container tightly closed and in a cool, well-ventilated

place. Use properly labelled and closeable containers. Store at

ambient temperature.

Product Transfer : This material has the potential to be a static accumulator.

Proper grounding and bonding procedures should be used

during all bulk transfer operations.

Recommended Materials : For containers or container linings, use mild steel or high

density polyethylene.

Unsuitable Materials : PVC.

Additional Information : Polyethylene containers should not be exposed to high

temperatures because of possible risk of distortion.

8. HAZARDOUS EXPOSURES DEBUGGING TOOLS AND PERSONAL PROTECTIVE EQUIPMENT

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

Occupational Exposure Limits

Material	Source	Туре	ppm	mg/m3	Notation
Oil mist, mineral	ACGIH	TWA(Inhala ble fraction.)		5 mg/m3	

Biological Exposure Index (BEI) - See reference for full details

No biological limit allocated.

Exposure Controls: The level of protection and types of controls necessary will vary

depending upon potential exposure conditions. Select controls

based on a risk assessment of local circumstances.

according to EC directive 2001/58/EC

Material Safety Data Sheet

Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne

recommended national standards. Check with PPE suppliers.

concentrations to be generated.

Personal Protective Equipment

Respiratory Protection

Personal protective equipment (PPE) should meet

No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65°C(149 °F)].

Hand Protection

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

Eye Protection

Wear safety glasses or full face shield if splashes are likely to

occur.

Protective Clothing

Skin protection not ordinarily required beyond standard issue

work clothes.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory. Examples of sources of

Material Safety Data Sheet

according to EC directive 2001/58/EC

recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/ Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/ Health and Safety Executive (HSE), UK: Methods for the

Determination of Hazardous Substances

http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen

Unfallversicherung (IFA), Germany. http://www.dguv.de/inhalt/index.isp

L'Institut National de Recherche et de Securité, (INRS), France

http://www.inrs.fr/accueil

Environmental Exposure

Controls

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

9. PHYSICOCHEMICAL PROPERTIES

Appearance : Light brown. Liquid at room temperature.

Odour Slight hydrocarbon. рΗ Not applicable.

Initial Boiling Point and

Boiling Range

: > 280 °C / 536 °F estimated value(s)

: Typical -30 °C / -22 °F Pour point

: Typical 230 °C / 446 °F (COC) Flash point : Typical 1 - 10 %(V) (based on mineral oil)

Upper / lower Flammability

or Explosion limits

Auto-ignition temperature $: > 320 \, ^{\circ}\text{C} / 608 \, ^{\circ}\text{F}$

: < 0,5 Pa at 20 °C / 68 °F (estimated value(s)) Vapour pressure

Specific gravity : Typical 0,868 at 15 °C / 59 °F Density : Typical 868 kg/m3 at 15 °C / 59 °F

Water solubility : Negligible.

n-octanol/water partition

coefficient (log Pow)

> 6 (based on information on similar products)

Kinematic viscosity : Typical 46 mm2/s at 40 °C / 104 °F : > 1 (estimated value(s)) Vapour density (air=1)

Evaporation rate (nBuAc=1) : Data not available

10. STABILITY AND REACTIVITY

: Stable. **Stability**

Conditions to Avoid : Extremes of temperature and direct sunlight.

Materials to Avoid : Strong oxidising agents.

: Hazardous decomposition products are not expected to form Hazardous

Decomposition Products during normal storage.

Print Date 17.11.2012 00000019506

according to EC directive 2001/58/EC

Material Safety Data Sheet

11. TOXICITY INFORMATION

Basis for Assessment : Information given is based on data on the components and the

toxicology of similar products.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

Acute Oral Toxicity
Acute Dermal Toxicity
Acute Inhalation Toxicity

Expected to be of low toxicity: LD50 > 5000 mg/kg, Rat Expected to be of low toxicity: LD50 > 5000 mg/kg, Rabbit Not considered to be an inhalation hazard under normal

conditions of use.

Skin Irritation
Eye Irritation

Respiratory Irritation : Inhalation

Sensitisation
Repeated Dose Toxicity

Mutagenicity

Carcinogenicity

Expected to be slightly irritating.

Inhalation of vapours or mists may cause irritation.

Not expected to be a skin sensitiser.

Expected to be slightly irritating.

Not expected to be a hazard.

Not considered a mutagenic hazard.

Not expected to be carcinogenic. Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on

Cancer (IARC).

Material	:	Carcinogenicity Classification
Highly refined mineral oil (IP346 <3%)	:	ACGIH Group A4: Not classifiable as a human carcinogen.
Highly refined mineral oil (IP346 <3%)	:	IARC 3: Not classifiable as to carcinogenicity to humans.
Highly refined mineral oil (IP346 <3%)	:	GHS / CLP: No carcinogenicity classification

Reproductive and Developmental Toxicity Additional Information

: Not expected to be a hazard.

: Used oils may contain harmful impurities that have

accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

12. ENVIRONMENTAL IMPACT INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Acute Toxicity : Poorly soluble mixture. May cause physical fouling of aquatic

organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) LL/EL50 expressed as the

according to EC directive 2001/58/EC

Material Safety Data Sheet

nominal amount of product required to prepare aqueous test extract. Mineral oil is not expected to cause any chronic effects

to aquatic organisms at concentrations less than 1 mg/l.

Mobility : Liquid under most environmental conditions. If it enters soil, it

will adsorb to soil particles and will not be mobile. Floats on

water.

Persistence/degradability : Expected to be not readily biodegradable. Major constituents

are expected to be inherently biodegradable, but the product contains components that may persist in the environment.

Bioaccumulation : Contains components with the potential to bioaccumulate.

Other Adverse Effects : Product is a mixture of non-volatile components, which are not

expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical

ozone creation potential or global warming potential.

13. DISCHARGE OF WASTES RECOMMENDATIONS

Material Disposal : Recover or recycle if possible. It is the responsibility of the

waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in

drains or in water courses.

Container Disposal : Dispose in accordance with prevailing regulations, preferably to

a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Local Legislation : Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

14. TRANSPORTATION INFORMATION

ADR

This material is not classified as dangerous under ADR regulations.

RID

This material is not classified as dangerous under RID regulations.

ADN

This material is not classified as dangerous under ADN regulations.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.

Additional Information: MARPOL Annex 1 rules apply for bulk shipments by sea.

according to EC directive 2001/58/EC

15. INFORMATION ABOUT INTERNATIONAL AND NATIONAL LEGISLATIONS

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

EC Classification : Not classified as dangerous under EC criteria.

EC Symbols : No Hazard Symbol required

EC Risk Phrases : Not classified. EC Safety Phrases : Not classified.

Chemical Inventory Status

EINECS : All components

listed or polymer

exempt.

TSCA : All components

listed.

16. ADDITIONAL INFORMATION

R-phrase(s)

Not classified.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

SDS Version Number : 1.1

SDS Effective Date : 15.11.2012

SDS Revisions : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

SDS Regulation : The content and format of this safety data sheet is in

accordance with Notification of Ministry of Industry, Subject: Hazard Classification and Communication System of

Hazardous Substances B.E.2555 (2012).

1. GN 2.2.5.1313-03 "Maximum permissible concentration of

harmful substance in the working zone area".

2. GOST 12.1.007-76 "Harmful agents. Classification and safety

requirements."

3. GOST 12.1.005-88 "General hygiene requirements to the

working zone area".

4. GN 2.1.5.1315-03 "Reservoir water maximum permissible

concentration".

5. GOST 19433-88 "Dangerous goods. Classification and

marking".

6. Rail transportation safety rules and dangerous doogs

accidents liquidation procedure.

7. GOST 30333-2007 Chemical product safety data sheet.

Shell Corena S3 R 46

Version 1.1

Effective Date 15.11.2012

according to EC directive 2001/58/EC

Material Safety Data Sheet

General requirements.

SDS Distribution : The information in this document should be made available to

all who may handle the product.

Disclaimer : This information is based on our current knowledge and is

intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property

of the product.