

NO. 1109-00013K-02

For Medium Vacuum Range
High Grade Vacuum pump Oil for Oil Sealed Rotary Pump

NEOVAC MR-200

NEOVAC MR-200 is high grade vacuum rotary pump oil which is prepared by the fractional distillation of highly refined mineral base oil in MORESCO's unique molecular distiller.

NEOVAC MR-200 is standard vacuum rotary pump oil for versatile purposes.

Characteristics

1. Low vapor pressure Enables pumps to obtain the ultimate pressure as low as rotary pump can attain.
2. Excellent demulsibility Separates moisture readily.
3. Excellent oxidation stability... Can be expected long term fluid service, Minimizes maintenance job due to the Formation of sludge.

General Properties of NEOVAC MR Series.

Item	MR-200
Density 15°C g/cm ³	0.883
Flash Point °C	256
Viscosity 40°C mm ² /SEC(cSt)	71.0
Color (ASTM)	L0.5
Pour Point °C	-17.5
Emulsion Characteristics	40-40-0(Below 5)
Vapor Pressure 50°C Pa	Below 1.3×10 ⁻³
Thermal Stability 170°C × 24h.	Pass

Some Applications

Versatile uses in most of the industries.

Package

20L pail can, 200L drum.

株式会社 **MORESCO** URL: <http://www.moresco.co.jp/>

東京支店 〒104-0028 東京都中央区八重洲2丁目8-5 釜淵八重洲ビル8階 ☎03-3273-7526
 大阪支店 〒541-0051 大阪市中央区備後町3丁目2-15 モレスコ本町ビル7階 ☎06-6262-3310
 小山営業所 〒323-0022 栃木県小山市駅東通1丁目4-3 小山駅東口ビル2階 ☎0285-23-9372
 名古屋営業所 〒460-0002 名古屋市中区丸の内1丁目15-9 第20KTビル10階 ☎052-222-3235
 九州営業所 〒830-0044 福岡県久留米市本町4-33 明治安田生命久留米本町ビル3階 ☎0942-30-7734
 研究センター 〒650-0047 神戸市中央区港島南町5丁目5-3 ☎078-303-9010
 カスタマーセンター E-mail: customercenter@moresco.co.jp ☎06-6262-3385

MORESCO Corporation

Head Office :5-5-3, Minatojiminami-machi, Chuo-ku, Kobe-city, Hyogo, Japan, 650-0047
 R&D Center Phone:078-303-9010 Fax:078-303-9020
 Tokyo Branch:Ryoshinyaesu-Bldg., 2-8-5, Yaesu, Chuo-ku, Tokyo, Japan, 104-0028
 (International Business Division) Phone:03-3273-7526 Fax:03-3281-7756