

TECHNICAL INFORMATION **MOLYguard**

MOLYguard SNV/RM Special

Synthetic blended oil for conveyor chains.

MOLYguard SNV/RM Special is a synthetic oil for conveyor chain working in high temperature.

Due its special formulation it's studied for the chain lubrication in high temperature also where the heating is made by gas.

MOLYguard SNV/RM Special has a mixture of synthetic base that allow to the oil to avoid any type of carbon residual and guarantee a perfect lubrication.

The development and the continue research permit the introduction into the formula of the new type of additives specially for the auto cleaning action.

MOLYguard SNV/RM Special allows a good reduction of oil consumption, due to the low evaporation.

Remove all type of residual from the chain coming to the previous oil.

MOLYguard SNV/RM Special It is special study for MDF conveyor chain.

Technical data:

Base Oil	:	Blended synthetic base
Viscosity ISO VG	:	100 to 460
Color	:	Yellow dark transparent
Viscosity Index	:	140
AGMA	:	5EP
Viscosity ASTM D445, D2161		
40°C cts	:	Check specific table
100°C cts	:	Check specific table
Flash point ASTM D 92	:	>260
Pour Point ASTM D 97	:	-30°C
Volatility ASTM D 972 in % di peso perso	:	27/60
22 hr a 60°C	:	0
22 hr a 149°C	:	0,13
22 hr a 204°C	:	3,8
Water resistance	:	OK