

Stenol Premium 220

High Performance Conveyor Chain Oil

Benefits :

- Complete lubrication in hard to reach areas due to excellent penetrating properties.
- Being synthetic oil the chain remains clean due to low residue formation and carbonization.
- Oil does not drip and soil the parts even at high operating temperatures of (+) 250°C.

Applications :

- Conveyor Chains operating under heavy loads and high temperatures.
- Slide ways, open bearings, transmission chains for paint booths, drying & varnishing plants, stenters, and powder coating machines.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Clear
Colour	Visual	–	Pale Yellow
Density @ 27°C	*CTM	gms/cc	0.94±0.05
Viscosity @ 40°C @ 100°C	ASTM D-445	cSt cSt	220 18
Flash Point	ASTM D-92	°C	280
Pour Point [min.]	ASTM D-97	°C	-15
Evaporation Loss @ 200°C for 6 hrs.	*CTM	%	< 5
Operating Temperature	–	°C	(+) 250

*CTM=Corporate Test Method

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product.

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.0/11.12.17]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

Anand Engineers Pvt Ltd. 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com